

TABLE 1. DASH NUMBERS AND DIMENSIONS

DASH NUMBER	DIMENSIONS		SCREW [✓] THREAD SIZE	WEIGHT LBS PER 1000	
	A	B			
-1	.438	.062	4-40	4.0	
-2	.469	.093		4.1	
-3	.500	.125		4.2	
-4	.562	.187		4.3	
-5	.625	.250		6-32	5.0
-6	.688	.312			5.1
-7		.375			5.2
-8 ^{2/}	.750	OVER .375	5.3		
-9	.438	.062	5.4		
-10	.469	.093			
-11	.500	.125			
-12	.562	.187			
-13	.625	.250			
-14	.688	.312			
-15	.750	.375			
-16 ^{2/}		OVER .375			

[✓] SEE REQUIREMENT 5
^{2/} SEE NOTE 2

ⓑ ENTIRE STANDARD REVISED


USER ACTIVITIES:
REVIEWER ACTIVITIES:
ARMY-AV,ER
NAVY-AS
DLA-IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense.
Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P A NAVY-AS Other Curt ARMY-AV AIR FORCE-99	INTERNATIONAL INTEREST	TITLE NUT, SHEET SPRING, INSTRUMENT MOUNTING	MILITARY STANDARD MS33737	
			PROCUREMENT SPECIFICATION MIL-N-3336	SUPERSEDES NAS 487
			PAGE 1 OF 2	

REQUIREMENTS:

1. MATERIAL: CASE, PHOSPHOR BRONZE, COMPOSITION A OR D SPRING TEMPER (UNS C51000), (UNS C52400) AND (UNS C54400), IN ACCORDANCE WITH QQ-B-750. NUT, HALF-HARD BRASS (UNS C26000) AND (UNS C34000) IN ACCORDANCE WITH QQ-B-626.
2. FINISH: CADMIUM PLATE IN ACCORDANCE WITH QQ-P-416, TYPE II, CLASS 2 WHERE SPECIFIED.
3. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
4. TOLERANCES: TOLERANCES UNLESS SPECIFIED: $\pm .010$.
5. MOUNTING SCREW: USE MS35214 SCREW OR SIMILAR FOR MOUNTING OF WHICH THE LENGTH SHALL BE DIMENSION G PLUS .250 INCH. THE NUT NEED NOT HAVE THE SHAPE SHOWN, BUT MUST BE CONTAINED WITHIN THE OUTLINE SHOWN.
6. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MG NUMBER, FOLLOWED BY A DASH NUMBER FROM TABLE I AND A FINISH CODE LETTER.



MS33737-1C INDICATES - NUT, SHEET SPRING, INSTRUMENT MOUNTING; .438; CADMIUM PLATE.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. FOR CONFIGURATION OF -8 AND -16 SEE TYPICAL INSTALLATION ILLUSTRATION.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

USER ACTIVITIES:

REVIEWER ACTIVITIES:
ARMY-AV,ER
NAVY-AS
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. NAVY-AS <small>Other Dist</small> ARMY-AV AIR FORCE-99	INTERNATIONAL INTEREST	TITLE NUT, SHEET SPRING, INSTRUMENT MOUNTING	MILITARY STANDARD
PROCUREMENT SPECIFICATION MIL-N-3336	SUPERSEDES.	NAS 487	MS33737
		PAGE 2	OF 2

APPROVED 17 JUN 64 REVISED 64 FOR CHANGES SEE PAGES 1 AND 2