

FED. SUPPLY CLASS
5306

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1000 WILSON BLVD.
ARLINGTON, VA 22209




FIGURE 1 - BOLT CONFIGURATION

TABLE I - DIMENSIONS

10

BASIC NUMBER	THREAD UNJF-3A	C		ØD		ØE MIN /10/	H +.015 - .000	J +.015 - .000	ØK /17/	M ±.010
		MAX	MIN	MAX	MIN					
NAS6203	.1900-32	.376	.367	.1895	.1885	.335	.110	.073	.056 .046	.164
NAS6204	.2500-28	.439	.429	.2495	.2485	.398	.125	.083		.170
NAS6205	.3125-24	.502	.492	.3120	.3110	.460	.156	.104	.080 .070	.182
NAS6206	.3750-24	.564	.554	.3745	.3735	.523	.188	.125		.183
NAS6207	.4375-20	.690	.678	.4370	.4360	.648	.219	.146	.199	
NAS6208	.5000-20	.752	.741	.4995	.4985	.710	.250	.167	.198	
NAS6209	.5625-18	.877	.865	.5615	.5605	.835	.281	.188	.207	
NAS6210	.6250-18	.940	.928	.6240	.6230	.898	.312	.208	.207	
NAS6212	.7500-16	1.065	1.052	.7490	.7480	1.023	.375	.250	.222	
NAS6214	.8750-14	1.252	1.239	.8740	.8730	1.210	.438	.292	.241	
NAS6216	1.0000-12	1.440	1.427	.9990	.9980	1.398	.500	.333	.264	
NAS6218	1.1250-12	1.627	1.614	1.1240	1.1225	1.585	.562	.375	.295	
NAS6220	1.2500-12	1.814	1.801	1.2490	1.2475	1.772	.625	.417	.295	

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09-01

REVISION DATE: DECEMBER 20, 2013
ISSUE DATE: FEBRUARY 1969



Reproduced By IHS
With The Permission Of AIA/NAS
Under Royalty Agreement

THIRD ANGLE PROJECTION	CUSTODIAN NATIONAL AEROSPACE STANDARDS COMMITTEE	REVISION 10
PROCUREMENT SPECIFICATION NOTED	TITLE BOLT, TENSION, HEX HEAD, CLOSE TOLERANCE, ALLOY STEEL, SHORT THREAD, REDUCED MAJOR THREAD DIA., SELF-LOCKING AND NONLOCKING, 160 KSI Ftu	CLASSIFICATION PART STANDARD NAS6203 THRU NAS6220 SHEET 1 OF 7

USE OF OR RELIANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR CERTIFY CONFORMANCE OF ITEMS PRODUCED UNDER NATIONAL AEROSPACE STANDARDS. AIA MAKES NO REPRESENTATION OR CLAIM RESPECTING (1) THE SUITABILITY OF ITEMS FOR ANY PARTICULAR APPLICATION OR (2) THE EXISTENCE OF OR APPLICABILITY THEREOF OF PATENT OR TRADEMARKS RIGHTS.

TABLE I - DIMENSIONS (CONTINUED)

BASIC NUMBER	ØN ±.01	ØP ±.005 /9/	R		(T) /2/	ØTD		U MAX	W MIN	X /7/	Y /8/	INSPECTION DATA		
			MAX	MIN		MAX	MIN					AA /4/	BB /5/	CC /4/
NAS6203	.19	.075	.020	.010	.323	.1840	.1810	.039	.410	.156	.094	.0045	.0040	.005
NAS6204	.25	.081	.020	.010	.370	.2440	.2410	.045	.480	.179	.107	.0045	.0030	.006
NAS6205	.31	.081	.020	.010	.438	.3060	.3020	.052	.552	.208	.125	.0045	.0030	.008
NAS6206	.38	.111	.025	.015	.454	.3680	.3640	.052	.623	.208	.125	.0045	.0025	.009
NAS6207	.44	.111	.025	.015	.528	.4310	.4260	.062	.764	.250	.150	.0060	.0025	.010
NAS6208	.50	.111	.030	.020	.528	.4930	.4880	.062	.836	.250	.150	.0060	.0020	.011
NAS6209	.56	.146	.035	.020	.594	.5550	.5500	.068	.978	.278	.167	.0060	.0020	.012
NAS6210	.62	.146	.040	.025	.626	.6180	.6120	.068	1.050	.278	.167	.0060	.0020	.015
NAS6212	.75	.146	.045	.030	.666	.7430	.7370	.078	1.191	.312	.188	.0060	.0020	.018
NAS6214	.88	.146	.050	.035	.759	.8680	.8610	.089	1.405	.357	.214	.0090	.0020	.020
NAS6216	1.00	.146	.060	.045	.895	.9930	.9860	.104	1.619	.417	.250	.0090	.0020	.022
NAS6218	1.12	.146	.070	.055	.989	1.1180	1.1110	.104	1.832	.417	.250	.0090	.0020	.025
NAS6220	1.25	.146	.075	.060	1.083	1.2430	1.2360	.104	2.046	.417	.250	.0090	.0020	.028

MATERIAL: ALLOY STEEL - 4140 (UNS G41400) PER AMS6349 OR AMS6382, 4340 (UNS G43406) PER AMS6415 OR AMS6484 OR 8740 (UNS G87400) PER AMS6322 OR MIL-S-6049, (10) AMS6325 OR AMS6327.

LOCKING ELEMENT - NYLON OR EQUIVALENT PER MIL-DTL-18240 AND QPL-18240.

HEAT TREAT: DEVELOP BASIC MATERIAL PROPERTIES AS FOLLOWS, WITH CONTROLS PER AMS-H-6875 OR AMS2759:
160 - 180 KSI Ft_u

FINISH: CADMIUM PLATED BOLTS - CADMIUM PLATE PER AMS-QQ-P-416, TYPE II, CLASS 2. EMBRITTLEMENT REQUIREMENT PER NAS4002.

CHROMIUM PLATED BOLTS - CHROMIUM PLATE PER AMS-QQ-C-320, CLASS 2 ON SHANK ONLY. ALL OTHER SURFACES CADMIUM PLATED. NO CHROMIUM WITHIN .020 OF LINE OF TANGENCY OF HEAD TO SHANK FILLET. CHROMIUM IN THREAD RUNOUT PERMITTED. CHROMIUM PLATED BOLTS NOT AVAILABLE WITH GRIP DASH NUMBER 1 OR NUMBER 2.

CODE: NO FINISH CODE AFTER BASIC NUMBER FOR CADMIUM PLATED BOLTS.
ADD "C" AFTER BASIC NUMBER FOR CHROMIUM PLATED BOLTS.
ADD "L" AFTER BASIC NUMBER FOR SELF-LOCKING BOLT WITH LOCKING ELEMENT TYPE OPTIONAL;
SEE PROCUREMENT SPEC BELOW. DO NOT USE "L" WITH "D" OR "P" CODE.
ADD "P" AFTER BASIC NUMBER FOR SELF-LOCKING BOLT WITH PATCH TYPE LOCKING ELEMENT ONLY;
SEE PROCUREMENT SPEC BELOW. DO NOT USE "P" WITH "D" OR "L" CODE.
GRIP DASH NUMBER INDICATES GRIP IN .0625 INCREMENTS (CONVERTED TO THREE DECIMAL PLACES PER ANSI Y14.5-1982). SEE TABLE II FOR TABULATIONS OF GRIP AND LENGTH DIMENSIONS. /15/
(10) ADD "D" AFTER GRIP DASH NUMBER FOR DRILLED THREAD BOLTS. DO NOT USE WITH "L" OR "P" CODE. /12/
ADD "H" AFTER GRIP DASH NUMBER FOR BOLT WITH DRILLED HEAD.
CODE LETTER "X" AND "Y" FOLLOWING THE GRIP DASH NUMBER INDICATES REPLACEMENT OVERSIZE REPAIR BOLT. (SEE LAST SHEET)
IF MORE THAN ONE CODE LETTER IS USED IN SEQUENCE, ARRANGE THE LETTERS ALPHABETICALLY.

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC
1000 WILSON BLVD.
ARLINGTON, VA 22209

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09 01

REVISION
10
NAS6203 THRU NAS6220
SHEET 2

EXAMPLE OF PART NUMBER: (SEE LAST SHEET FOR OVERSIZE BOLTS.)

⑩	NAS6204-10	= BOLT, .2500-28 THREAD, .625 GRIP, UNDRILLED, NONLOCKING, CADMIUM PLATED.
	NAS6204-10D	= BOLT, .2500-28 THREAD, .625 GRIP, DRILLED THREAD, NONLOCKING, CADMIUM PLATED.
	NAS6204-10DH	= BOLT, .2500-28 THREAD, .625 GRIP, DRILLED THREAD, DRILLED HEAD, NONLOCKING, CADMIUM PLATED.
	NAS6204C10H	= BOLT, .2500-28 THREAD, .625 GRIP, DRILLED HEAD, UNDRILLED THREAD, NONLOCKING, CHROMIUM PLATED.
	NAS6204L10	= BOLT, .2500-28 THREAD, .625 GRIP, UNDRILLED, SELF-LOCKING (LOCKING TYPE OPTIONAL), CADMIUM PLATED.
	NAS6204P10	= BOLT, .2500-28 THREAD, .625 GRIP, UNDRILLED, SELF-LOCKING (PATCH TYPE), CADMIUM PLATED.
	NAS6204C10	= BOLT, .2500-28 THREAD, .625 GRIP, UNDRILLED, NONLOCKING, CHROMIUM PLATED.

NOTES:

- /1/ GRIP LENGTH: FROM UNDER SIDE OF HEAD TO END OF FULL CYLINDRICAL PORTION OF SHANK.
- /2/ REFERENCE DIMENSIONS ARE FOR DESIGN PURPOSES ONLY AND ARE NOT AN INSPECTION REQUIREMENT.
- /3/ BEARING SURFACE SQUARENESS: WITHIN .003 FIM OF "ØD".
- /4/ CONCENTRICITY: "ØD" AND MAJOR THREAD DIA WITHIN "AA" VALUES FIM. "ØD" AND "ØE" WITHIN "CC" VALUES FIM.
- /5/ SHANK STRAIGHTNESS: WITHIN "BB" VALUES FIM PER INCH OF LENGTH.
- /6/ PROTRUSION OF LOCKING ELEMENT SHALL BE CONTROLLED SO THAT IT WILL PASS FREELY, OR WITH FINGER PRESSURE, THROUGH A RING GAGE WITH DIAMETER OF .010 (+.001, -.000) GREATER THAN MAXIMUM MAJOR DIAMETER OF BOLT THREAD.
- ⑩ /7/ "X" MIN (5 THREAD PITCHES) = REGION OF MINIMUM ENGAGEMENT WITH INTERNAL THREAD REQUIRED TO MEET MIL-DTL-18240 REQUIREMENTS. LOCKING ELEMENT WITHIN "X" REGION MUST DEVELOP REQUIRED TORQUE WHEN TESTED PER MIL-DTL-18240.
- /8/ FOR EASE IN STARTING, LOCKING ELEMENT SHALL NOT BE EFFECTIVE IN "Y" AREA (3 THREAD PITCHES).
- /9/ "ØP" HOLE CENTERLINE WITHIN .010 AND NORMAL WITHIN 2° OF BOLT CENTERLINE.
- ⑩ /10/ "ØE" MAX NOT TO EXCEED ACTUAL WIDTH ACROSS FLATS; MIN AS TABULATED IN TABLE I.
- ~~(11) PLATING THICKNESS MINIMUM TO BE .0003 PER AMS QQ-P-416, CLASS 2.~~
- ⑩ /12/ IF REQUIRED, TENSILE TESTING OF BOLTS REQUIRING CROSS-DRILLED THREADS SHALL BE PERFORMED PRIOR TO DRILLING AND THE APPLICATION OF PLATING AND/OR COATINGS. WHEN BOLTS HAVE BEEN DRILLED, STRENGTH MAY BE VERIFIED BY SHEAR TESTING, IN LIEU OF TENSILE TESTING, IN ACCORDANCE WITH NASM1312. USERS SHOULD BE AWARE THAT FASTENERS WITH CROSS-DRILLED THREADS MAY EXHIBIT A REDUCTION IN TENSILE STRENGTH.

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1000 WILSON BLVD.
ARLINGTON, VA 22209

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09-01

REVISION
10
NAS6203 THRU NAS6220
SHEET 3



NATIONAL AEROSPACE STANDARD

© COPYRIGHT 2013 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED



- ⑩ /13/ HEAD MARKING: BASIC NUMBER PLUS GRIP DASH NUMBER PLUS "D", "L", OR "P", WHEN APPLICABLE, PLUS MANUFACTURER'S SYMBOL, RAISED OR DEPRESSED .010 MAX. ARRANGEMENT OPTIONAL.
 "D" IDENTIFIES BOLT WITH DRILLED THREAD.
 "L" IDENTIFIES BOLT WITH LOCKING ELEMENT (OPTIONAL TYPE).
 "P" IDENTIFIES BOLT WITH PATCH TYPE LOCKING ELEMENT ONLY.
 "C", CHROMIUM PLATED CODE NEED NOT APPEAR ON BOLT HEAD.
- ⑩ (14) SURFACE ROUGHNESS: "ØD", BEARING SURFACE OF HEAD, THREAD FLANKS AND THREAD ROOT: 32 MICROINCHES Ra; ALL OTHER SURFACES: 125 MICROINCHES Ra PER ASME B46.1.
 /15/ INTERMEDIATE OR LONGER LENGTHS MAY BE SPECIFIED BY THE USE OF WHOLE GRIP DASH NUMBERS ONLY. NOMINAL LENGTH EQUALS NOMINAL GRIP PLUS "T".
- ⑩ (16) DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
- /17/ LOCKWIRE HOLES SHALL BE DRILLED WITHIN .010 OF CENTER OF HEX FLAT WHEN SPECIFIED BY PART NUMBER.
- ⑩ (18) DIMENSIONS IN INCHES AND APPLY AFTER FINISH UNLESS OTHERWISE SPECIFIED.
- (19) REMOVE ALL BURRS AND SHARP EDGES.
- (20) THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
- ⑩ (21) UNLESS OTHERWISE SPECIFIED HEREIN, REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF MANUFACTURE. HOWEVER, EXISTING MATERIAL INVENTORY CERTIFIED TO A PREVIOUS REVISION OF THE APPLICABLE MATERIAL SPECIFICATION(S) IS ACCEPTABLE FOR USE UNTIL DEPLETION.
- (22) UNLESS OTHERWISE SPECIFIED, PART INVENTORY MANUFACTURED TO PREVIOUS REVISIONS OF THE APPLICABLE DRAWING OR SPECIFICATION MAY BE PROCURED AND USED UNTIL STOCK IS DEPLETED.

PROCUREMENT SPECIFICATION:

NAS4002, EXCEPT AS NOTED. COLD WORK OF HEAD TO SHANK FILLET RADIUS AND FATIGUE TESTING ARE NOT REQUIRED FOR NAS6203 BOLTS. LOCKING ELEMENT FOR SELF-LOCKING BOLTS: PER NASM15981 AND MIL-DTL-18240. LOCKING ELEMENT TYPE, INCLUDING PATCH TYPE, IS OPTIONAL WHEN "L" CODE IS SPECIFIED. PATCH TYPE LOCKING ELEMENT (WITH NO METAL REMOVED) IS REQUIRED WHEN "P" CODE IS SPECIFIED. LOCKING ELEMENT MUST BE SUPPLIED BY A QUALIFIED SOURCE LISTED IN QPL-18240 OR APPROVED FOR LISTING IN QPL-18240. SHIPPING NOTICE SHOULD IDENTIFY SUPPLIER OF BOLT AND LOCKING ELEMENT SEPARATELY.

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1000 WILSON BLVD.
ARLINGTON, VA 22209

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09-01

REVISION
10
NAS6203 THRU NAS6220
SHEET 4



NATIONAL AEROSPACE STANDARD

© COPYRIGHT 2013 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED



TABLE II - GRIP AND LENGTH DIMENSIONS

GRIP DASH NO.	GRIP ±.010	LENGTH ± .015 /15/												
		BASIC NUMBER AND THREAD SIZE												
		NAS6203	NAS6204	NAS6205	NAS6206	NAS6207	NAS6208	NAS6209	NAS6210	NAS6212	NAS6214	NAS6216	NAS6218	NAS6220
		.1900-32	.2500-28	.3125-24	.3750-24	.4375-20	.5000-20	.5625-18	.6250-18	.7500-16	.8750-14	1.0000-12	1.1250-12	1.2500-12
1	.062	.385	.432	.500	.516	.590	.590	.656	.688	.728	.821	.957	1.051	1.145
2	.125	.448	.495	.563	.579	.653	.653	.719	.751	.791	.884	1.020	1.114	1.208
3	.188	.511	.558	.626	.642	.716	.716	.782	.814	.854	.947	1.083	1.177	1.271
4	.250	.573	.620	.688	.704	.778	.778	.844	.876	.916	1.009	1.145	1.239	1.333
5	.312	.635	.682	.750	.766	.840	.840	.906	.938	.978	1.071	1.207	1.301	1.395
6	.375	.698	.745	.813	.829	.903	.903	.969	1.001	1.041	1.134	1.270	1.364	1.458
7	.438	.761	.808	.876	.892	.966	.966	1.032	1.064	1.104	1.197	1.333	1.427	1.521
8	.500	.823	.870	.938	.954	1.028	1.028	1.094	1.126	1.166	1.259	1.395	1.489	1.583
9	.562	.885	.932	1.000	1.016	1.090	1.090	1.156	1.188	1.228	1.321	1.457	1.551	1.645
10	.625	.948	.995	1.063	1.079	1.153	1.153	1.219	1.251	1.291	1.384	1.520	1.614	1.708
11	.688	1.011	1.058	1.126	1.142	1.216	1.216	1.282	1.314	1.354	1.447	1.583	1.677	1.771
12	.750	1.073	1.120	1.188	1.204	1.278	1.278	1.344	1.376	1.416	1.509	1.645	1.739	1.833
13	.812	1.135	1.182	1.250	1.266	1.340	1.340	1.406	1.438	1.478	1.571	1.707	1.801	1.895
14	.875	1.198	1.245	1.313	1.329	1.403	1.403	1.469	1.501	1.541	1.634	1.770	1.864	1.958
15	.938	1.261	1.308	1.376	1.392	1.466	1.466	1.532	1.564	1.604	1.697	1.833	1.927	2.021
16	1.000	1.323	1.370	1.438	1.454	1.528	1.528	1.594	1.626	1.666	1.759	1.895	1.989	2.083
17	1.062	1.385	1.432	1.500	1.516	1.590	1.590	1.656	1.688	1.728	1.821	1.957	2.051	2.145
18	1.125	1.448	1.495	1.563	1.579	1.653	1.653	1.719	1.751	1.791	1.884	2.020	2.114	2.208
19	1.188	1.511	1.558	1.626	1.642	1.716	1.716	1.782	1.814	1.854	1.947	2.083	2.177	2.271
20	1.250	1.573	1.620	1.688	1.704	1.778	1.778	1.844	1.876	1.916	2.009	2.145	2.239	2.333
21	1.312	1.635	1.682	1.750	1.766	1.840	1.840	1.906	1.938	1.978	2.071	2.207	2.301	2.395
22	1.375	1.698	1.745	1.813	1.829	1.903	1.903	1.969	2.001	2.041	2.134	2.270	2.364	2.458
23	1.438	1.761	1.808	1.876	1.892	1.966	1.966	2.032	2.064	2.104	2.197	2.333	2.427	2.521
24	1.500	1.823	1.870	1.938	1.954	2.028	2.028	2.094	2.126	2.166	2.259	2.395	2.489	2.583
25	1.562	1.885	1.932	2.000	2.016	2.090	2.090	2.156	2.188	2.228	2.321	2.457	2.551	2.645
26	1.625	1.948	1.995	2.063	2.079	2.153	2.153	2.219	2.251	2.291	2.384	2.520	2.614	2.708
27	1.688	2.011	2.058	2.126	2.142	2.216	2.216	2.282	2.314	2.354	2.447	2.583	2.677	2.771
28	1.750	2.073	2.120	2.188	2.204	2.278	2.278	2.344	2.376	2.416	2.509	2.645	2.739	2.833
29	1.812	2.135	2.182	2.250	2.266	2.340	2.340	2.406	2.438	2.478	2.571	2.707	2.801	2.895
30	1.875	2.198	2.245	2.313	2.329	2.403	2.403	2.469	2.501	2.541	2.634	2.770	2.864	2.958
31	1.938	2.261	2.308	2.376	2.392	2.466	2.466	2.532	2.564	2.604	2.697	2.833	2.927	3.021
32	2.000	2.323	2.370	2.438	2.454	2.528	2.528	2.594	2.626	2.666	2.759	2.895	2.989	3.083
34	2.125	2.448	2.495	2.563	2.579	2.653	2.653	2.719	2.751	2.791	2.884	3.020	3.114	3.208
36	2.250	2.573	2.620	2.688	2.704	2.778	2.778	2.844	2.876	2.916	3.009	3.145	3.239	3.333

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1000 WILSON BLVD.
ARLINGTON, VA 22209

10

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09-01

REVISION
10
NAS6203 THRU NAS6220
SHEET 5



NATIONAL AEROSPACE STANDARD

© COPYRIGHT 2013 AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC. ALL RIGHTS RESERVED



TABLE II - GRIP AND LENGTH DIMENSIONS (CONTINUED)

GRIP DASH NO.	GRIP ±.010	LENGTH ± .015 /15/													
		BASIC NUMBER AND THREAD SIZE													
		NAS6203	NAS6204	NAS6205	NAS6206	NAS6207	NAS6208	NAS6209	NAS6210	NAS6212	NAS6214	NAS6216	NAS6218	NAS6220	
		.1900-32	.2500-28	.3125-24	.3750-24	.4375-20	.5000-20	.5625-18	.6250-18	.7500-16	.8750-14	1.0000-12	1.1250-12	1.2500-12	
38	2.375	2.698	2.745	2.813	2.829	2.903	2.903	2.969	3.001	3.041	3.134	3.270	3.364	3.458	
40	2.500	2.823	2.870	2.938	2.954	3.028	3.028	3.094	3.126	3.166	3.259	3.395	3.489	3.583	
42	2.625	2.948	2.995	3.063	3.079	3.153	3.153	3.219	3.251	3.291	3.384	3.520	3.614	3.708	
44	2.750	3.073	3.120	3.188	3.204	3.278	3.278	3.344	3.376	3.416	3.509	3.645	3.739	3.833	
46	2.875	3.198	3.245	3.313	3.329	3.403	3.403	3.469	3.501	3.541	3.634	3.770	3.864	3.958	
48	3.000	3.323	3.370	3.438	3.454	3.528	3.528	3.594	3.626	3.666	3.759	3.895	3.989	4.083	
50	3.125	3.448	3.495	3.563	3.579	3.653	3.653	3.719	3.751	3.791	3.884	4.020	4.114	4.208	
52	3.250	3.573	3.620	3.688	3.704	3.778	3.778	3.844	3.876	3.916	4.009	4.145	4.239	4.333	
54	3.375	3.698	3.745	3.813	3.829	3.903	3.903	3.969	4.001	4.041	4.134	4.270	4.364	4.458	
56	3.500	3.823	3.870	3.938	3.954	4.028	4.028	4.094	4.126	4.166	4.259	4.395	4.489	4.583	
58	3.625	3.948	3.995	4.063	4.079	4.153	4.153	4.219	4.251	4.291	4.384	4.520	4.614	4.708	
60	3.750	4.073	4.120	4.188	4.204	4.278	4.278	4.344	4.376	4.416	4.509	4.645	4.739	4.833	
62	3.875	4.198	4.245	4.313	4.329	4.403	4.403	4.469	4.501	4.541	4.634	4.770	4.864	4.958	
64	4.000	4.323	4.370	4.438	4.454	4.528	4.528	4.594	4.626	4.666	4.759	4.895	4.989	5.083	
66	4.125	4.448	4.495	4.563	4.579	4.653	4.653	4.719	4.751	4.791	4.884	5.020	5.114	5.208	
68	4.250	4.573	4.620	4.688	4.704	4.778	4.778	4.844	4.876	4.916	5.009	5.145	5.239	5.333	
70	4.375	4.698	4.745	4.813	4.829	4.903	4.903	4.969	5.001	5.041	5.134	5.270	5.364	5.458	
72	4.500	4.823	4.870	4.938	4.954	5.028	5.028	5.094	5.126	5.166	5.259	5.395	5.489	5.583	
74	4.625	4.948	4.995	5.063	5.079	5.153	5.153	5.219	5.251	5.291	5.384	5.520	5.614	5.708	
76	4.750	5.073	5.120	5.188	5.204	5.278	5.278	5.344	5.376	5.416	5.509	5.645	5.739	5.833	
78	4.875	5.198	5.245	5.313	5.329	5.403	5.403	5.469	5.501	5.541	5.634	5.770	5.864	5.958	
80	5.000	5.323	5.370	5.438	5.454	5.528	5.528	5.594	5.626	5.666	5.759	5.895	5.989	6.083	
82	5.125	5.448	5.495	5.563	5.579	5.653	5.653	5.719	5.751	5.791	5.884	6.020	6.114	6.208	
84	5.250	5.573	5.620	5.688	5.704	5.778	5.778	5.844	5.876	5.916	6.009	6.145	6.239	6.333	
86	5.375	5.698	5.745	5.813	5.829	5.903	5.903	5.969	6.001	6.041	6.134	6.270	6.364	6.458	
88	5.500	5.823	5.870	5.938	5.954	6.028	6.028	6.094	6.126	6.166	6.259	6.395	6.489	6.583	
90	5.625	5.948	5.995	6.063	6.079	6.153	6.153	6.219	6.251	6.291	6.384	6.520	6.614	6.708	
92	5.750	6.073	6.120	6.188	6.204	6.278	6.278	6.344	6.376	6.416	6.509	6.645	6.739	6.833	
94	5.875	6.198	6.245	6.313	6.329	6.403	6.403	6.469	6.501	6.541	6.634	6.770	6.864	6.958	
96	6.000	6.323	6.370	6.438	6.454	6.528	6.528	6.594	6.626	6.666	6.759	6.895	6.989	7.083	

AEROSPACE INDUSTRIES ASSOCIATION OF AMERICA, INC.
1000 WILSON BLVD.
ARLINGTON, VA 22209

THIS DRAWING SUPERSEDES ALL ANTECEDENT STANDARD DRAWINGS FOR THE SAME PRODUCT AND SHALL BECOME EFFECTIVE NO LATER THAN SIX MONTHS FROM THE LAST REVISION DATE.

FORM 09-01

REVISION
10
NAS6203 THRU NAS6220
SHEET 6

USE OF OR RELIANCE UPON THIS DOCUMENT OR ANY NATIONAL AEROSPACE STANDARD IS ENTIRELY VOLUNTARY. AIA DOES NOT QUALIFY SUPPLIERS OR CERTIFY CONFORMANCE OF ITEMS PRODUCED UNDER NATIONAL AEROSPACE STANDARDS. AIA MAKES NO REPRESENTATION OR CLAIM RESPECTING (1) THE SUITABILITY OF ITEMS FOR ANY PARTICULAR APPLICATION OR (2) THE EXISTENCE OF OR APPLICABILITY THEREOF OF PATENT OR TRADEMARKS RIGHTS.