

CAT and CEET Ducting

Wire supported aircraft quality ducting-neoprene impregnated fiberglass types
temperature range -65° F to +350° F.

Part No.	Dash Number	Inside Diameter
CAT4	4	1"
CEET4	4	1"
CAT5	5	1 ¼"
CEET5	5	1 ¼"
CAT6	6	1 ½"
CEET6	6	1 ½"
CAT7	7	1 ¾"
CEET7	7	1 ¾"
CAT8	8	2"
CEET8	8	2"
CAT9	9	2 ¼"
CEET9	9	2 ¼"
CAT10	10	2 ½"
CEET10	10	2 ½"
CAT11	11	2 ¾"
CEET11	11	2 ¾"
CAT12	12	3"
CEET12	12	3"
CAT13	13	3 ¼"
CEET13	13	3 ¼"
CAT14	14	3 ½"
CEET14	14	3 ½"
CAT15	15	3 ¾"
CEET15	15	3 ¾"
CAT16	16	4"
CEET16	16	4"
CAT18	18	4 ½"
CEET18	18	4 ½"
CAT20	20	5"
CEET20	20	5"
CAT22	22	5 ½"
CEET22	22	5 ½"
CAT24	24	6"
CEET24	24	6"
CAT26	26	6 ½"
CEET26	26	6 ½"
CAT28	28	7"
CEET28	28	7"
CAT32	32	8"
CEET 32	32	8"
CAT40	40	10"
CEET40	40	10"
CAT48	48	12"
CEET48	48	12"

Note: Standard length is 10 feet. Larger and smaller diameters are available. Other types of ducting not shown.

SCAT and SCEET

Wire supported aircraft quality ducting silicone impregnated fiberglass types
temperature range -80° F to + 550° F.

Part No.	Dash Number	Inside Diameter
SCAT4	4	1"
SCEET4	4	1"
SCAT5	5	1 ¼"
SCEET5	5	1 ¼"
SCAT6	6	1 ½"
SCEET6	6	1 ½"
SCAT7	7	1 ¾"
SCEET7	7	1 ¾"
SCAT8	8	2"
SCEET8	8	2"
SCAT9	9	2 ¼"
SCEET9	9	2 ¼"
SCAT10	10	2 ½"
SCEET10	10	2 ½"
SCAT11	11	2 ¾"
SCEET11	11	2 ¾"
SCAT12	12	3"
SCEET12	12	3"
SCAT13	13	3 ¼"
SCEET13	13	3 ¼"
SCAT14	14	3 ½"
SCEET14	14	3 ½"
SCAT15	15	3 ¾"
SCEET15	15	3 ¾"
SCAT16	16	4"
SCEET16	16	4"
SCAT18	18	4 ½"
SCEET18	18	4 ½"
SCAT20	20	5"
SCEET20	20	5"
SCAT22	22	5 ½"
SCEET22	22	5 ½"
SCAT24	24	6"
SCEET24	24	6"

Note: Standard length is 11 feet. Other types of ducting are available. Soft cuffs are per each end. Larger and smaller diameters available.